

BILANCELLA

designed by Roberto Giacomucci

512.21 Sospensione - Pendant

Collezione / Series

Bilancella

Dimensioni / Dimensions

H. 3 x Ø. 50 / H. 1.2" x Ø. 19.7"

Peso / Weight

3,3 kg / 7,3 lb

Materiali / Materials

metal

CE  IP40

Certificazioni / Certifications

CE (240V)

Sorgente / Source

220/240 V

Integrated LED

Wattage: 38 Watts

Lumens: 3000 lm

Color Temperature: 2700K

Cable: 150 cm

Note / Notes

Custom ceiling plate on request

Only in 220/240V

Nr. 3 ceiling attachments included

Finiture / Finishes

C74 Sand black

Struttura a sospensione realizzata in metallo da un piatto diffusore circolare e da un rosone. Fornita con cavo in tessuto..

Pendant lamp with structure made of metal by a circular diffuser plate and a canopy. Supplied with fabric cable.

ABOUT

Lampada a sospensione, soffitto e parete con diffusore in metallo verniciato a polveri epossidiche di spessore molto sottile.

La versione decentrata, presenta un sistema di fissaggio a soffitto versatile che permette di illuminare anche in assenza di punti luce predisposti a soffitto. I decentratori in metallo infatti, permettono al filo elettrico di scorrere per portare la luce dove occorre. Grazie alla sua essenziale forma, la luce si diffonde uniformemente in tutto l'ambiente.

Suspension, ceiling and wall lamp with a thin metal powder coated diffuser. The decentrate version has a versatile ceiling mounting system allowing to illuminate even in absence of electrical connection on the ceiling. In addition, the metal decentralizers allow the wire to slide to bring the light where it is needed. Thanks to its essential form, the light spreads evenly throughout the environment.



BILANCELLA

512.21 Pendant

Picture on page 87 of the catalogue

Design: Roberto Giacomucci

Description: Pendant with a thin metal powder coated diffuser. Thanks to its essential form, the light spreads evenly throughout the environment.

Materials: metal

Mounting: Pendant: cable length 150 cm. Cable: 3 x 0,75 mm². Canopy: Ø 13 cm included with bracket.

Nt. Wt.: 3,3 kg

Class: Degree of protection IP40, insulation class 1.

Note: Custom canopy on request

CE ⊕ IP40




code	source	lumens	dimmiability	finishes	cable (cm)	dimensions (cm)	LED
512.21	LED 220/240V	3000 Lm	/	C74	150	H 3 x Ø 50	38W 2700K

Hardware



C74 Sand black



measurements in mm